

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

建設機械等
損料算定表

P101

- 101 -

頁番号		現 行																			摘 要	
分 類 コ ー ド		規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運転日 当り 標準運 転時間 (時間)	t 供用日 当り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転 1 時間当り 損 料 額 (円)	(11) 供用 1 日当り 損 料 額 (円)	参 考			摘 要		
		諸 元	機 関 出 力 (kW)	機 械 質 量 (t)				(3) 運 転 時 間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)							(13) 運転 1 時間当り 換 算 値 損 料 額 (円)	(15) 供用 1 日当り 換 算 値 損 料 額 (円)				
建設機械等 損料算定表 P101	- 101 -	065-036	500～650	35	55×2	11.8	30,200	10.0	0.9	570	90	140	6.3	4.1	20	10.0	3,440	36,000	12,200	50,000	[510]油圧押込機構を含み、排土キャップ、オーガスクリュ及びオーガヘッドは含まない。	
		085-045	650～850	45	75×2	12.5	41,500	10.0	0.9	570	90	140	6.3	4.1	20	10.0	4,730	49,500	16,800	68,700		
		090-045	800～900	45	90×2	13.0	44,000	10.0	0.9	570	90	140	6.3	4.1	20	10.0	5,020	52,400	17,800	72,800		
		510 【アースオーガ中掘式】																				
		100-045	杭径 φ400～1,000mm	オーガ出力 45kW	45	15.4	9,600	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,130	9,600	3,720	13,800		
		120-055	400～1,200	55	55	19.0	12,200	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,440	12,200	4,740	17,500		
		120-090	400～1,200	90	90	19.8	15,700	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,850	15,800	6,120	22,500		
		120-110	600～1,200	55×2	55×2	24.3	15,900	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,880	15,900	6,180	22,800		
		610 【アースオーガ併用鋼矢板圧入機】																			[610]制御盤、操作盤及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。	
		045-001	オーガ出力 45kW	適応鋼矢板 Ⅱ～Ⅴ型	45	8.6	26,700	11.5	0.9	590	90	160	6.6	3.7	35	10.0	3,150	26,700	10,400	38,300		
		055-001	55	Ⅱ～Ⅴ	55	8.9	29,400	11.5	0.9	590	90	160	6.6	3.7	35	10.0	3,470	29,400	11,400	42,200		
		619 【0505-610付属機器】																				
		201-002	【ケーシング】 (各種)		—	—	—	11.5	0.9	590	90	160	6.6	3.7	35	10.0	—	—	—	—	[0509]低騒音型機械を含む。	
		(ベースマシン損料)																				
		0509 クローラ式杭打機 (ベースマシン)																				
		011 【直結三点支持式】																				
				リーダ長 14.5～15.5m	全装備質量 43t	86	31.3	49,400	11.5	0.9	690	120	180	5.8	3.8	30	10.0	4,690	43,900	16,200	61,800	機械質量の訂正
				18～21	66	117	34.3	69,100	11.5	0.9	690	120	180	5.8	3.8	30	10.0	6,560	61,400	22,700	86,500	
				21～24	88	92	41.5	73,700	11.5	0.9	690	120	180	5.8	3.8	30	10.0	7,000	65,600	24,300	92,200	
				21～27	95	114	46.1	89,300	11.5	0.9	690	120	180	5.8	3.8	30	10.0	8,480	79,400	29,400	112,000	
		21～33	105	114	51.0	111,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	10,500	98,700	36,500	139,000			
		21～33	120	136	60.7	116,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	11,000	103,000	38,100	145,000			
		21～36	135	147	65.3	126,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	12,000	112,000	41,500	158,000			
		21～39	160	159	76.0	161,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	15,300	143,000	52,900	201,000			
		21～36	180	147	84.5	188,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	17,900	167,000	61,800	235,000			

改 訂

- 101 -

コード		05																			コード		05																			摘 要	
分 類 コ ー ド		規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運転日 当り 標準運 転時間 (時間)	t 供用日 当り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転 1 時間当り 損 料 額 (円)	(11) 供用 1 日当り 損 料 額 (円)	参 考			摘 要																							
		諸 元	機 関 出 力 (kW)	機 械 質 量 (t)				(3) 運 転 時 間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)							(13) 運転 1 時間当り 換 算 値 損 料 額 (円)	(15) 供用 1 日当り 換 算 値 損 料 額 (円)																									
建設機械等 損料算定表 P101	- 101 -	065-036	500～650	35	55×2	11.8	30,200	10.0	0.9	570	90	140	6.3	4.1	20	10.0	3,440	36,000	12,200	50,000	[510]油圧押込機構を含み、排土キャップ、オーガスクリュ及びオーガヘッドは含まない。																						
		085-045	650～850	45	75×2	12.5	41,500	10.0	0.9	570	90	140	6.3	4.1	20	10.0	4,730	49,500	16,800	68,700																							
		090-045	800～900	45	90×2	13.0	44,000	10.0	0.9	570	90	140	6.3	4.1	20	10.0	5,020	52,400	17,800	72,800																							
		510 【アースオーガ中掘式】																																									
		100-045	杭径 φ400～1,000mm	オーガ出力 45kW	45	15.4	9,600	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,130	9,600	3,720	13,800																							
		120-055	400～1,200	55	55	19.0	12,200	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,440	12,200	4,740	17,500																							
		120-090	400～1,200	90	90	19.8	15,700	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,850	15,800	6,120	22,500																							
		120-110	600～1,200	55×2	55×2	24.3	15,900	11.5	0.9	590	90	160	6.6	3.7	35	10.0	1,880	15,900	6,180	22,800																							
		610 【アースオーガ併用鋼矢板圧入機】																			[610]制御盤、操作盤及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。																						
		045-001	オーガ出力 45kW	適応鋼矢板 Ⅱ～Ⅴ型	45	8.6	26,700	11.5	0.9	590	90	160	6.6	3.7	35	10.0	3,150	26,700	10,400	38,300																							
		055-001	55	Ⅱ～Ⅴ	55	8.9	29,400	11.5	0.9	590	90	160	6.6	3.7	35	10.0	3,470	29,400	11,400	42,200																							
		619 【0505-610付属機器】																																									
		201-002	【ケーシング】 (各種)		—	—	—	11.5	0.9	590	90	160	6.6	3.7	35	10.0	—	—	—	—	[0509]低騒音型機械を含む。																						
		(ベースマシン損料)																																									
		0509 クローラ式杭打機 (ベースマシン)																																									
		011 【直結三点支持式】																																									
				リーダ長 14.5～15.5m	全装備質量 43t	86	33.5	49,400	11.5	0.9	690	120	180	5.8	3.8	30	10.0	4,690	43,900	16,200	61,800	機械質量の訂正																					
				18～21	66	117	51.9	69,100	11.5	0.9	690	120	180	5.8	3.8	30	10.0	6,560	61,400	22,700	86,500																						
				21～24	88	92	57.6	73,700	11.5	0.9	690	120	180	5.8	3.8	30	10.0	7,000	65,600	24,300	92,200																						
				21～27	95	114	72.9	89,300	11.5	0.9	690	120	180	5.8	3.8	30	10.0	8,480	79,400	29,400	112,000																						
		21～33	105	114	77.7	111,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	10,500	98,700	36,500	139,000																								
		21～33	120	136	90.7	116,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	11,000	103,000	38,100	145,000																								
		21～36	135	147	102	126,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	12,000	112,000	41,500	158,000																								
		21～39	160	159	121	161,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	15,300	143,000	52,900	201,000																								
		21～36	180	147	130	188,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	17,900	167,000	61,800	235,000																								

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

頁番号	現 行																				摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
建設機械等 損料算定表 P102	<table><tr><th colspan="2">コード</th><th colspan="2">05</th><th colspan="10"></th><th colspan="2">コード</th><th colspan="2">05</th><th colspan="2"></th></tr><tr><th colspan="2">分 類 コ ー ド</th><th colspan="3">規 格</th><th>(1)</th><th>(2)</th><th rowspan="2">償 却 費 率</th><th colspan="3">年 間 標 準</th><th>T 運 転 日 当 り 標準運 転 時間</th><th>t 供 用 日 当 り 標準運 転 時間</th><th>(6)</th><th>(7)</th><th>(9)</th><th>(11)</th><th colspan="2">参 考</th><th colspan="2"></th></tr><tr><th colspan="3">諸 元</th><th>機 関 出 力 (kW)</th><th>機 械 質 量 (t)</th><th>基礎価格 (千円)</th><th>標準 使用 年数 (年)</th><th>(3)</th><th>(4)</th><th>(5)</th><th>(%)</th><th>(%)</th><th>運 転 1 時間 当り 損 料 額 (円)</th><th>供 用 1 日 当り 損 料 額 (円)</th><th>(13)</th><th>(15)</th><th colspan="2">摘 要</th></tr><tr><td colspan="3">031 〔多関節バックホウ・リーダレス型（軌跡制御機能付）〕</td><td colspan="18"></td><td>[031]1kN±0.102t 1kN・m±0.102t・m</td></tr><tr><td>160-001</td><td colspan="3">適応ハーフ・ロハンマ 適応アースオーガ 油圧式 起振力 油圧式 最大掘削トルク 160kN級 26kN・m級</td><td>116</td><td>23.0</td><td>45,700</td><td>11.5</td><td>0.9</td><td>690</td><td>120</td><td>180</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>4,340</td><td>40,600</td><td>15,000</td><td>57,200</td><td></td></tr><tr><td>200-001</td><td colspan="3">200 60</td><td>202</td><td>37.1</td><td>100,000</td><td>11.5</td><td>0.9</td><td>690</td><td>120</td><td>180</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>9,500</td><td>88,900</td><td>32,900</td><td>125,000</td><td></td></tr><tr><td colspan="20">(組合せ損料＝単体＋ベースマシン)</td><td></td></tr><tr><td colspan="20">0511 クローラ式杭打機</td><td></td></tr><tr><td colspan="3">011 〔ディーゼルハンマ・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>350-001</td><td colspan="3">ラム質量 リーダ長 吊能力 3.5t 18～21m 35～40t</td><td>117</td><td>42.9</td><td>72,800</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>7,430</td><td>68,500</td><td>25,500</td><td>96,400</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="3">031 〔ディーゼルハンマ・ブーム式〕</td><td colspan="18"></td><td></td></tr><tr><td>130-001</td><td colspan="3">ラム質量 リーダ長 吊能力 1.3t 18m 16t</td><td>117</td><td>37.4</td><td>50,700</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>5,170</td><td>47,700</td><td>17,700</td><td>67,200</td><td></td></tr><tr><td>250-001</td><td colspan="3">2.5 19 25</td><td>117</td><td>39.8</td><td>55,100</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>5,620</td><td>51,900</td><td>19,300</td><td>73,000</td><td></td></tr><tr><td colspan="3">041 〔ディーゼルハンマ及びアースオーガ併用・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>136-001</td><td colspan="3">ラム質量 オーク径/出力 リーダ長 1.3t φ320～600mm/30kW 18～21m</td><td>117</td><td>40.2</td><td>82,800</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,450</td><td>77,900</td><td>29,000</td><td>110,000</td><td>[041]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。継足しホルダを使用する場合は、基礎価格に780千円を加算する。</td></tr><tr><td>138-001</td><td colspan="3">1.3 320～800 /45 18～21</td><td>117</td><td>43.7</td><td>86,400</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,810</td><td>81,300</td><td>30,200</td><td>114,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="3">410 〔パイプロハンマ及びアースオーガ併用・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>226-001</td><td colspan="3">ハーフ出力 オーク径/出力 リーダ長 22kW φ320～600mm/30kW 18～21m</td><td>117</td><td>39.2</td><td>82,100</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,370</td><td>77,300</td><td>28,700</td><td>109,000</td><td>[410]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。</td></tr><tr><td>306-001</td><td colspan="3">30 320～600/30 18～21</td><td>117</td><td>39.7</td><td>83,400</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,510</td><td>78,400</td><td>29,100</td><td>110,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td>456-001</td><td colspan="3">45 320～600/30 18～21</td><td>117</td><td>41.1</td><td>84,900</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,660</td><td>79,800</td><td>29,700</td><td>112,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td>606-001</td><td colspan="3">60 320～600/30 18～21</td><td>117</td><td>42.1</td><td>88,900</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>9,070</td><td>83,600</td><td>31,100</td><td>118,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="3">510 〔モンケン及びアースオーガ併用・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>206-001</td><td colspan="3">モンケン質量 オーク径/出力 リーダ長 2t φ320～600mm/30kW 14.5～15.5m</td><td>86</td><td>36.3</td><td>58,600</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>5,980</td><td>55,100</td><td>20,500</td><td>77,600</td><td>[510]真矢を含む。制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。</td></tr><tr><td>208-001</td><td colspan="3">2 350～800/45 18～21</td><td>117</td><td>42.8</td><td>81,900</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,350</td><td>77,100</td><td>28,600</td><td>109,000</td><td>ベースマシンは全装備質量66t。</td></tr></table>																				コード		05												コード		05				分 類 コ ー ド		規 格			(1)	(2)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転 時間	t 供 用 日 当 り 標準運 転 時間	(6)	(7)	(9)	(11)	参 考				諸 元			機 関 出 力 (kW)	機 械 質 量 (t)	基礎価格 (千円)	標準 使用 年数 (年)	(3)	(4)	(5)	(%)	(%)	運 転 1 時間 当り 損 料 額 (円)	供 用 1 日 当り 損 料 額 (円)	(13)	(15)	摘 要		031 〔多関節バックホウ・リーダレス型（軌跡制御機能付）〕																					[031]1kN±0.102t 1kN・m±0.102t・m	160-001	適応ハーフ・ロハンマ 適応アースオーガ 油圧式 起振力 油圧式 最大掘削トルク 160kN級 26kN・m級			116	23.0	45,700	11.5	0.9	690	120	180	5.8	3.8	30	10.0	4,340	40,600	15,000	57,200		200-001	200 60			202	37.1	100,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	9,500	88,900	32,900	125,000		(組合せ損料＝単体＋ベースマシン)																					0511 クローラ式杭打機																					011 〔ディーゼルハンマ・直結三点支持式〕																						350-001	ラム質量 リーダ長 吊能力 3.5t 18～21m 35～40t			117	42.9	72,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	7,430	68,500	25,500	96,400	ベースマシンは全装備質量66t。	031 〔ディーゼルハンマ・ブーム式〕																						130-001	ラム質量 リーダ長 吊能力 1.3t 18m 16t			117	37.4	50,700	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,170	47,700	17,700	67,200		250-001	2.5 19 25			117	39.8	55,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,620	51,900	19,300	73,000		041 〔ディーゼルハンマ及びアースオーガ併用・直結三点支持式〕																						136-001	ラム質量 オーク径/出力 リーダ長 1.3t φ320～600mm/30kW 18～21m			117	40.2	82,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,450	77,900	29,000	110,000	[041]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。継足しホルダを使用する場合は、基礎価格に780千円を加算する。	138-001	1.3 320～800 /45 18～21			117	43.7	86,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,810	81,300	30,200	114,000	ベースマシンは全装備質量66t。	410 〔パイプロハンマ及びアースオーガ併用・直結三点支持式〕																						226-001	ハーフ出力 オーク径/出力 リーダ長 22kW φ320～600mm/30kW 18～21m			117	39.2	82,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,370	77,300	28,700	109,000	[410]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。	306-001	30 320～600/30 18～21			117	39.7	83,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,510	78,400	29,100	110,000	ベースマシンは全装備質量66t。	456-001	45 320～600/30 18～21			117	41.1	84,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,660	79,800	29,700	112,000	ベースマシンは全装備質量66t。	606-001	60 320～600/30 18～21			117	42.1	88,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	9,070	83,600	31,100	118,000	ベースマシンは全装備質量66t。	510 〔モンケン及びアースオーガ併用・直結三点支持式〕																						206-001	モンケン質量 オーク径/出力 リーダ長 2t φ320～600mm/30kW 14.5～15.5m			86	36.3	58,600	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,980	55,100	20,500	77,600	[510]真矢を含む。制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。	208-001	2 350～800/45 18～21			117	42.8	81,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,350	77,100	28,600	109,000	ベースマシンは全装備質量66t。	
	コード		05												コード		05																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
	分 類 コ ー ド		規 格			(1)	(2)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転 時間	t 供 用 日 当 り 標準運 転 時間	(6)	(7)	(9)	(11)	参 考																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
	諸 元			機 関 出 力 (kW)	機 械 質 量 (t)	基礎価格 (千円)	標準 使用 年数 (年)		(3)	(4)	(5)	(%)	(%)	運 転 1 時間 当り 損 料 額 (円)	供 用 1 日 当り 損 料 額 (円)	(13)	(15)	摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
	031 〔多関節バックホウ・リーダレス型（軌跡制御機能付）〕																					[031]1kN±0.102t 1kN・m±0.102t・m																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
	160-001	適応ハーフ・ロハンマ 適応アースオーガ 油圧式 起振力 油圧式 最大掘削トルク 160kN級 26kN・m級			116	23.0	45,700	11.5	0.9	690	120	180	5.8	3.8	30	10.0	4,340	40,600	15,000	57,200																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
	200-001	200 60			202	37.1	100,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	9,500	88,900	32,900	125,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
	(組合せ損料＝単体＋ベースマシン)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
	0511 クローラ式杭打機																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
	011 〔ディーゼルハンマ・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
	350-001	ラム質量 リーダ長 吊能力 3.5t 18～21m 35～40t			117	42.9	72,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	7,430	68,500	25,500	96,400	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	031 〔ディーゼルハンマ・ブーム式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
	130-001	ラム質量 リーダ長 吊能力 1.3t 18m 16t			117	37.4	50,700	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,170	47,700	17,700	67,200																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
	250-001	2.5 19 25			117	39.8	55,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,620	51,900	19,300	73,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
	041 〔ディーゼルハンマ及びアースオーガ併用・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
	136-001	ラム質量 オーク径/出力 リーダ長 1.3t φ320～600mm/30kW 18～21m			117	40.2	82,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,450	77,900	29,000	110,000	[041]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。継足しホルダを使用する場合は、基礎価格に780千円を加算する。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	138-001	1.3 320～800 /45 18～21			117	43.7	86,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,810	81,300	30,200	114,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	410 〔パイプロハンマ及びアースオーガ併用・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
	226-001	ハーフ出力 オーク径/出力 リーダ長 22kW φ320～600mm/30kW 18～21m			117	39.2	82,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,370	77,300	28,700	109,000	[410]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	306-001	30 320～600/30 18～21			117	39.7	83,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,510	78,400	29,100	110,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	456-001	45 320～600/30 18～21			117	41.1	84,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,660	79,800	29,700	112,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	606-001	60 320～600/30 18～21			117	42.1	88,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	9,070	83,600	31,100	118,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
	510 〔モンケン及びアースオーガ併用・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
206-001	モンケン質量 オーク径/出力 リーダ長 2t φ320～600mm/30kW 14.5～15.5m			86	36.3	58,600	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,980	55,100	20,500	77,600	[510]真矢を含む。制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
208-001	2 350～800/45 18～21			117	42.8	81,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,350	77,100	28,600	109,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
改 訂																					摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
<table><tr><th colspan="2">コード</th><th colspan="2">05</th><th colspan="10"></th><th colspan="2">コード</th><th colspan="2">05</th><th colspan="2"></th></tr><tr><th colspan="2">分 類 コ ー ド</th><th colspan="3">規 格</th><th>(1)</th><th>(2)</th><th rowspan="2">償 却 費 率</th><th colspan="3">年 間 標 準</th><th>T 運 転 日 当 り 標準運 転 時間</th><th>t 供 用 日 当 り 標準運 転 時間</th><th>(6)</th><th>(7)</th><th>(9)</th><th>(11)</th><th colspan="2">参 考</th><th colspan="2"></th></tr><tr><th colspan="3">諸 元</th><th>機 関 出 力 (kW)</th><th>機 械 質 量 (t)</th><th>基礎価格 (千円)</th><th>標準 使用 年数 (年)</th><th>(3)</th><th>(4)</th><th>(5)</th><th>(%)</th><th>(%)</th><th>運 転 1 時間 当り 損 料 額 (円)</th><th>供 用 1 日 当り 損 料 額 (円)</th><th>(13)</th><th>(15)</th><th colspan="2">摘 要</th></tr><tr><td colspan="3">031 〔多関節バックホウ・リーダレス型（軌跡制御機能付）〕</td><td colspan="18"></td><td>[031]1kN±0.102t 1kN・m±0.102t・m</td></tr><tr><td>160-001</td><td colspan="3">適応ハーフ・ロハンマ 適応アースオーガ 油圧式 起振力 油圧式 最大掘削トルク 160kN級 26kN・m級</td><td>116</td><td>23.0</td><td>45,700</td><td>11.5</td><td>0.9</td><td>690</td><td>120</td><td>180</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>4,340</td><td>40,600</td><td>15,000</td><td>57,200</td><td></td></tr><tr><td>200-001</td><td colspan="3">200 60</td><td>202</td><td>37.1</td><td>100,000</td><td>11.5</td><td>0.9</td><td>690</td><td>120</td><td>180</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>9,500</td><td>88,900</td><td>32,900</td><td>125,000</td><td></td></tr><tr><td colspan="20">(組合せ損料＝単体＋ベースマシン)</td><td></td></tr><tr><td colspan="20">0511 クローラ式杭打機</td><td></td></tr><tr><td colspan="3">011 〔ディーゼルハンマ・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>350-001</td><td colspan="3">ラム質量 リーダ長 吊能力 3.5t 18～21m 35～40t</td><td>117</td><td>60.7</td><td>72,800</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>7,430</td><td>68,500</td><td>25,500</td><td>96,400</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="3">031 〔ディーゼルハンマ・ブーム式〕</td><td colspan="18"></td><td></td></tr><tr><td>130-001</td><td colspan="3">ラム質量 リーダ長 吊能力 1.3t 18m 16t</td><td>117</td><td>25.6</td><td>50,700</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>5,170</td><td>47,700</td><td>17,700</td><td>67,200</td><td></td></tr><tr><td>250-001</td><td colspan="3">2.5 19 25</td><td>117</td><td>45.8</td><td>55,100</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>5,620</td><td>51,900</td><td>19,300</td><td>73,000</td><td></td></tr><tr><td colspan="3">041 〔ディーゼルハンマ及びアースオーガ併用・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>136-001</td><td colspan="3">ラム質量 オーク径/出力 リーダ長 1.3t φ320～600mm/30kW 18～21m</td><td>117</td><td>59.0</td><td>82,800</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,450</td><td>77,900</td><td>29,000</td><td>110,000</td><td>[041]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。継足しホルダを使用する場合は、基礎価格に780千円を加算する。</td></tr><tr><td>138-001</td><td colspan="3">1.3 320～800 /45 18～21</td><td>117</td><td>62.5</td><td>86,400</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,810</td><td>81,300</td><td>30,200</td><td>114,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="3">410 〔パイプロハンマ及びアースオーガ併用・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>226-001</td><td colspan="3">ハーフ出力 オーク径/出力 リーダ長 22kW φ320～600mm/30kW 18～21m</td><td>117</td><td>58.0</td><td>82,100</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,370</td><td>77,300</td><td>28,700</td><td>109,000</td><td>[410]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。</td></tr><tr><td>306-001</td><td colspan="3">30 320～600/30 18～21</td><td>117</td><td>58.5</td><td>83,400</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,510</td><td>78,400</td><td>29,100</td><td>110,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td>456-001</td><td colspan="3">45 320～600/30 18～21</td><td>117</td><td>59.9</td><td>84,900</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,660</td><td>79,800</td><td>29,700</td><td>112,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td>606-001</td><td colspan="3">60 320～600/30 18～21</td><td>117</td><td>60.9</td><td>88,900</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>9,070</td><td>83,600</td><td>31,100</td><td>118,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="3">510 〔モンケン及びアースオーガ併用・直結三点支持式〕</td><td colspan="18"></td><td></td></tr><tr><td>206-001</td><td colspan="3">モンケン質量 オーク径/出力 リーダ長 2t φ320～600mm/30kW 14.5～15.5m</td><td>86</td><td>39.7</td><td>58,600</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>5,980</td><td>55,100</td><td>20,500</td><td>77,600</td><td>[510]真矢を含む。制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。</td></tr><tr><td>208-001</td><td colspan="3">2 350～800/45 18～21</td><td>117</td><td>61.6</td><td>81,900</td><td>11.5</td><td>0.9</td><td>640</td><td>110</td><td>170</td><td>5.8</td><td>3.8</td><td>30</td><td>10.0</td><td>8,350</td><td>77,100</td><td>28,600</td><td>109,000</td><td>ベースマシンは全装備質量66t。</td></tr></table>																					コード		05												コード		05				分 類 コ ー ド		規 格			(1)	(2)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転 時間	t 供 用 日 当 り 標準運 転 時間	(6)	(7)	(9)	(11)	参 考				諸 元			機 関 出 力 (kW)	機 械 質 量 (t)	基礎価格 (千円)	標準 使用 年数 (年)	(3)	(4)	(5)	(%)	(%)	運 転 1 時間 当り 損 料 額 (円)	供 用 1 日 当り 損 料 額 (円)	(13)	(15)	摘 要		031 〔多関節バックホウ・リーダレス型（軌跡制御機能付）〕																					[031]1kN±0.102t 1kN・m±0.102t・m	160-001	適応ハーフ・ロハンマ 適応アースオーガ 油圧式 起振力 油圧式 最大掘削トルク 160kN級 26kN・m級			116	23.0	45,700	11.5	0.9	690	120	180	5.8	3.8	30	10.0	4,340	40,600	15,000	57,200		200-001	200 60			202	37.1	100,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	9,500	88,900	32,900	125,000		(組合せ損料＝単体＋ベースマシン)																					0511 クローラ式杭打機																					011 〔ディーゼルハンマ・直結三点支持式〕																						350-001	ラム質量 リーダ長 吊能力 3.5t 18～21m 35～40t			117	60.7	72,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	7,430	68,500	25,500	96,400	ベースマシンは全装備質量66t。	031 〔ディーゼルハンマ・ブーム式〕																						130-001	ラム質量 リーダ長 吊能力 1.3t 18m 16t			117	25.6	50,700	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,170	47,700	17,700	67,200		250-001	2.5 19 25			117	45.8	55,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,620	51,900	19,300	73,000		041 〔ディーゼルハンマ及びアースオーガ併用・直結三点支持式〕																						136-001	ラム質量 オーク径/出力 リーダ長 1.3t φ320～600mm/30kW 18～21m			117	59.0	82,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,450	77,900	29,000	110,000	[041]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。継足しホルダを使用する場合は、基礎価格に780千円を加算する。	138-001	1.3 320～800 /45 18～21			117	62.5	86,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,810	81,300	30,200	114,000	ベースマシンは全装備質量66t。	410 〔パイプロハンマ及びアースオーガ併用・直結三点支持式〕																						226-001	ハーフ出力 オーク径/出力 リーダ長 22kW φ320～600mm/30kW 18～21m			117	58.0	82,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,370	77,300	28,700	109,000	[410]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。	306-001	30 320～600/30 18～21			117	58.5	83,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,510	78,400	29,100	110,000	ベースマシンは全装備質量66t。	456-001	45 320～600/30 18～21			117	59.9	84,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,660	79,800	29,700	112,000	ベースマシンは全装備質量66t。	606-001	60 320～600/30 18～21			117	60.9	88,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	9,070	83,600	31,100	118,000	ベースマシンは全装備質量66t。	510 〔モンケン及びアースオーガ併用・直結三点支持式〕																						206-001	モンケン質量 オーク径/出力 リーダ長 2t φ320～600mm/30kW 14.5～15.5m			86	39.7	58,600	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,980	55,100	20,500	77,600	[510]真矢を含む。制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。	208-001	2 350～800/45 18～21			117	61.6	81,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,350	77,100	28,600	109,000	ベースマシンは全装備質量66t。	機械質量の訂正
コード		05												コード		05																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
分 類 コ ー ド		規 格			(1)	(2)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転 時間	t 供 用 日 当 り 標準運 転 時間	(6)	(7)	(9)	(11)	参 考																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
諸 元			機 関 出 力 (kW)	機 械 質 量 (t)	基礎価格 (千円)	標準 使用 年数 (年)		(3)	(4)	(5)	(%)	(%)	運 転 1 時間 当り 損 料 額 (円)	供 用 1 日 当り 損 料 額 (円)	(13)	(15)	摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
031 〔多関節バックホウ・リーダレス型（軌跡制御機能付）〕																					[031]1kN±0.102t 1kN・m±0.102t・m																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
160-001	適応ハーフ・ロハンマ 適応アースオーガ 油圧式 起振力 油圧式 最大掘削トルク 160kN級 26kN・m級			116	23.0	45,700	11.5	0.9	690	120	180	5.8	3.8	30	10.0	4,340	40,600	15,000	57,200																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
200-001	200 60			202	37.1	100,000	11.5	0.9	690	120	180	5.8	3.8	30	10.0	9,500	88,900	32,900	125,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
(組合せ損料＝単体＋ベースマシン)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
0511 クローラ式杭打機																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
011 〔ディーゼルハンマ・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
350-001	ラム質量 リーダ長 吊能力 3.5t 18～21m 35～40t			117	60.7	72,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	7,430	68,500	25,500	96,400	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
031 〔ディーゼルハンマ・ブーム式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
130-001	ラム質量 リーダ長 吊能力 1.3t 18m 16t			117	25.6	50,700	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,170	47,700	17,700	67,200																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
250-001	2.5 19 25			117	45.8	55,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,620	51,900	19,300	73,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
041 〔ディーゼルハンマ及びアースオーガ併用・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
136-001	ラム質量 オーク径/出力 リーダ長 1.3t φ320～600mm/30kW 18～21m			117	59.0	82,800	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,450	77,900	29,000	110,000	[041]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。継足しホルダを使用する場合は、基礎価格に780千円を加算する。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
138-001	1.3 320～800 /45 18～21			117	62.5	86,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,810	81,300	30,200	114,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
410 〔パイプロハンマ及びアースオーガ併用・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
226-001	ハーフ出力 オーク径/出力 リーダ長 22kW φ320～600mm/30kW 18～21m			117	58.0	82,100	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,370	77,300	28,700	109,000	[410]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
306-001	30 320～600/30 18～21			117	58.5	83,400	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,510	78,400	29,100	110,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
456-001	45 320～600/30 18～21			117	59.9	84,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,660	79,800	29,700	112,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
606-001	60 320～600/30 18～21			117	60.9	88,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	9,070	83,600	31,100	118,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
510 〔モンケン及びアースオーガ併用・直結三点支持式〕																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
206-001	モンケン質量 オーク径/出力 リーダ長 2t φ320～600mm/30kW 14.5～15.5m			86	39.7	58,600	11.5	0.9	640	110	170	5.8	3.8	30	10.0	5,980	55,100	20,500	77,600	[510]真矢を含む。制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、オーガスクリュ、オーガヘッドは含まない。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
208-001	2 350～800/45 18～21			117	61.6	81,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	8,350	77,100	28,600	109,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

頁番号	現 行																				摘 要														
建設機械等 損料算定表 P103	- 103 -	コード	05		規 格										(1)	(2)	償 却 費 率	年 間 標 準			T	t	(6)	(7)	(9)	(11)	参 考		コード	05		摘 要			
		分 類 コ ー ド			諸 元		機 関 出 力 (kW)	機 械 質 量 (t)	基礎価格 (千円)		標準 使用 年数 (年)	(3)	(4)	(5)	運 転 日 当 り 標準運 転時間 (時間)	供 用 日 当 り 標準運 転時間 (時間)		(%)	(%)	運 転 1 時 間 当 り 損 料 額 (円)	供 用 1 日 当 り 損 料 額 (円)	(13)	(15)	摘 要											
		610 〔油圧ハンマ・直結三点支持式〕				ラム質量 リータ`長 吊能力																						[610]油圧ユニット、油圧ホースを含む。							
			020-001	2t	14.5	15.5m	35	40t	ベ`ース 86 ハンマ 71	39.7	69,200	11.5	0.9	640	110	170	5.8	3.8	30	10.0	7,060	65,100	24,200	91,700	ベースマシンは全装備質量43t。										
			045-001	4	4.5	18	21	35	40	ハンマ 121 ベ`ース 92	48.9	98,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	10,100	93,000	34,600	131,000	ベースマシンは全装備質量66t。									
			080-001	6.5	8	21	24	45	50	ハンマ 132 ベ`ース 136	60.6	109,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	11,100	103,000	38,200	144,000	ベースマシンは全装備質量88t。									
			125-001	10	12.5	21	33	45	50	ハンマ 184	91.9	158,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	16,100	148,000	55,000	209,000	ベースマシンは全装備質量120t。									
		620 〔直/斜杭打ち兼用油圧ハンマ・直結三点支持式〕				ラム質量 リータ`長 吊能力																							[620]油圧ユニット、油圧ホースを含む。						
			115-001	11.5	12.5t	21	33m	60	65t	ハンマ 181 ベ`ース 136	95.4	188,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	19,200	177,000	65,800	249,000	ベースマシンは全装備質量120t。									
			150-001	15		21	33	80		ハンマ 235	101	194,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	19,800	183,000	68,000	257,000	ベースマシンは全装備質量120t。									
		710 〔鋼管ソイルセメント杭打機〕																											[710]同時沈設方式及び後沈設方式ともに、施工管理システム、駆動装置(掘削攪拌オーガ、鋼管回転装置)を含む。 ただし、同時沈設方式は、掘削攪拌ヘッド及びロッド、ロッドスタビライザ、スタビライザブラケット、鋼管回転キャップ・カラー、下部振れ止めは含まない。 後沈設方式は、掘削攪拌ヘッド及びロッド、鋼管定着用キャップは含まない。						
			110-001	杭径	最大施工深度	オーガ`出力				147	79.0	227,000	11.5	0.9	650	120	170	5.4	3.8	30	10.0	22,700	214,000	79,000	301,000	ベースマシンは全装備質量135t。									
		810 〔鋼管回転圧入機〕				全装備質量 掘削トルク 最大適合管長																							[810]施工管理装置を含む。						
			009-001	6	9t	43.7kN・m	(4.5t・m)	6m		35	8.7	40,900	9.5	0.9	740	120	170	6.2	4.4	30	10.0	4,380	40,800	13,700	59,800										
			016-001	11	16	67.9	(6.9)	6		66	13.4	56,100	9.5	0.9	740	120	170	6.2	4.4	30	10.0	6,000	55,900	18,700	82,000										
			030-001	25	30	274	(28.1)	10		92	30.6	86,000	9.5	0.9	740	120	170	6.2	4.4	30	10.0	9,200	85,800	28,700	126,000										
			055-001	50	55	548	(55.9)	10		209	54.8	134,000	9.5	0.9	740	120	170	6.2	4.4	30	10.0	14,300	133,000	44,500	196,000										
		819 〔0511-810付属機器〕																																	
			021-002	〔ヤットコロット〕		(各種)		—		—	—	3.7	0.92	—	—	180	—	—	30	8.0	—	—	—	—											
			022-002	〔鋼管キャップ〕		(各種)		—		—	—	3.7	0.92	—	—	180	—	—	30	8.0	—	—	—	—											
		改 訂																				摘 要													
		建設機械等 損料算定表 P103	- 103 -	コード	05		規 格										(1)	(2)	償 却 費 率	年 間 標 準			T	t	(6)	(7)	(9)	(11)	参 考		コード		05		機械質量の訂正
				分 類 コ ー ド			諸 元		機 関 出 力 (kW)	機 械 質 量 (t)	基礎価格 (千円)		標準 使用 年数 (年)	(3)	(4)	(5)	運 転 日 当 り 標準運 転時間 (時間)	供 用 日 当 り 標準運 転時間 (時間)		(%)	(%)	運 転 1 時 間 当 り 損 料 額 (円)	供 用 1 日 当 り 損 料 額 (円)	(13)	(15)	摘 要									
				610 〔油圧ハンマ・直結三点支持式〕				ラム質量 リータ`長 吊能力																							[610]油圧ユニット、油圧ホースを含む。				
					020-001	2t	14.5	15.5m	35	40t	ハンマ 71 ベ`ース 117	39.6	69,200	11.5	0.9	640	110	170	5.8	3.8	30	10.0	7,060	65,100	24,200	91,700	ベースマシンは全装備質量43t。								
					045-001	4	4.5	18	21	35	40	ハンマ 121 ベ`ース 92	62.4	98,900	11.5	0.9	640	110	170	5.8	3.8	30	10.0	10,100	93,000	34,600	131,000	ベースマシンは全装備質量66t。							
					080-001	6.5	8	21	24	45	50	ハンマ 132 ベ`ース 136	72.6	109,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	11,100	103,000	38,200	144,000	ベースマシンは全装備質量88t。							
					125-001	10	12.5	21	33	45	50	ハンマ 184	114	158,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	16,100	148,000	55,000	209,000	ベースマシンは全装備質量120t。							
				620 〔直/斜杭打ち兼用油圧ハンマ・直結三点支持式〕				ラム質量 リータ`長 吊能力																							[620]油圧ユニット、油圧ホースを含む。				
					115-001	11.5	12.5t	21	33m	60	65t	ハンマ 181 ベ`ース 136	113	188,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	19,200	177,000	65,800	249,000	ベースマシンは全装備質量120t。							
					150-001	15		21	33	80		ハンマ 235	119	194,000	11.5	0.9	640	110	170	5.8	3.8	30	10.0	19,800	183,000	68,000	257,000	ベースマシンは全装備質量120t。							
				710 〔鋼管ソイルセメント杭打機〕																											[710]同時沈設方式及び後沈設方式ともに、施工管理システム、駆動装置(掘削攪拌オーガ、鋼管回転装置)を含む。 ただし、同時沈設方式は、掘削攪拌ヘッド及びロッド、ロッドスタビライザ、スタビライザブラケット、鋼管回転キャップ・カラー、下部振れ止めは含まない。 後沈設方式は、掘削攪拌ヘッド及びロッド、鋼管定着用キャップは含まない。				
					110-001	杭径	最大施工深度	オーガ`出力				147	117	227,000	11.5	0.9	650	120	170	5.4	3.8	30	10.0	22,700	214,000	79,000	301,000	ベースマシンは全装備質量135t。							
				810 〔鋼管回転圧入機〕				全装備質量 掘削トルク 最大適合管長																							[810]施工管理装置を含む。				
					009-001	6	9t	43.7kN・m	(4.5t・m)	6m		35	8.7	40,900	9.5	0.9	740	120	170	6.2	4.4	30	10.0	4,380	40,800	13,700	59,800								
					016-001	11	16	67.9	(6.9)	6		66	13.4	56,100	9.5	0.9	740	120	170	6.2	4.4	30	10.0	6,000	55,900	18,700	82,000								
					030-001	25	30	274	(28.1)	10		92	30.6	86,000	9.5	0.9	740	120	170	6.2	4.4	30	10.0	9,200	85,800	28,700	126,000								
					055-001	50	55	548	(55.9)	10		209	54.8	134,000	9.5	0.9	740	120	170	6.2	4.4	30	10.0	14,300	133,000	44,500	196,000								
				819 〔0511-810付属機器〕																															
					021-002	〔ヤットコロット〕		(各種)		—		—	—	3.7	0.92	—	—	180	—	—	30	8.0	—	—	—	—									
					022-002	〔鋼管キャップ〕		(各種)		—		—	—	3.7	0.92	—	—	180	—	—	30	8.0	—	—	—	—									

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

建設機械等
損料算定表
P104

101

コード		05																		コード		05	
分類コード	規格	諸元	機関力 (kW)	機械質量 (t)	(1) 基礎価格 (千円)	(2) 標準使用 年数 (年)	償却 費率	年間標準			T	t	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転1時間当り 損料額 (円)	(11) 供用1日当り 損料額 (円)	参考		摘要				
								(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)	運転日 当り 標準運 転時間 (時間)	供用日 当り 標準運 転時間 (時間)					(13) 運転1時間当り 換算値 損料額 (円)	(15) 供用1日当り 換算値 損料額 (円)					
0512 クローラ式アースオーガ																							
111 【単軸式・直結三点支持式】																							
045-001	オーガ出力 掘削径 リーダ長 45kW φ 350～800mm 18～21m	117	40.8	81,400	11.5	0.9	630	110	160	5.7	3.9	30	10.0	8,470	81,400	29,300	115,000	ベースマシンは全装備質量66t。					
055-001	55 450～1,000 18～21	117	41.6	84,800	11.5	0.9	630	110	160	5.7	3.9	30	10.0	8,820	84,900	30,600	119,000	ベースマシンは全装備質量66t。					
075-001	75 450～1,000 21～27	114	53.6	106,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,000	106,000	38,200	149,000	ベースマシンは全装備質量95t。					
090-001	90 450～1,200 21～27	114	56.1	109,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,300	109,000	39,200	153,000	ベースマシンは全装備質量95t。					
110-001	55×2 450～1,200 21～33	114	62.3	132,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	13,700	132,000	47,500	186,000	ベースマシンは全装備質量105t。					
150-001	75×2 600～1,200 21～33	136	72.2	141,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,700	141,000	50,900	198,000	ベースマシンは全装備質量120t。					
180-001	90×2 600～1,800 21～33	136	74.4	159,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	16,500	159,000	57,300	224,000	ベースマシンは全装備質量120t。					
115 【単軸（油圧）式・直結三点支持式】																							
035-001	掘削トルク 掘削径 リーダ長 29～35kN・m φ 260～600mm 18～21m	117	36.4	78,600	11.5	0.9	630	110	160	5.7	3.9	30	10.0	8,170	78,700	28,300	111,000	ベースマシンは全装備質量66t。					
121 【二軸同軸式・直結三点支持式】																							
055-001	オーガ出力 掘削径 リーダ長 55kW φ 320～600m 21～27mm	114	53.5	107,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,100	107,000	38,500	151,000	ベースマシンは全装備質量95t。					
090-001	90 400～800 21～33	114	61.3	132,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	13,700	132,000	47,500	186,000	ベースマシンは全装備質量105t。					
110-001	55×2 800～1,200 21～33	136	74.7	150,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,600	151,000	54,300	211,000	ベースマシンは全装備質量120t。					
150-001	75×2 800～1,200 21～36	147	79.6	167,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	17,400	167,000	60,200	235,000	ベースマシンは全装備質量135t。					
180-001	90×2 800～1,500 21～36	147	79.8	169,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	17,600	169,000	60,900	238,000	ベースマシンは全装備質量135t。					
199 【0512-111～121付属機器】																							
023-002	【オーガスクリュ】 (各種)	—	—	—	1.7	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—						
024-002	【オーガヘッド】 (各種)	—	—	—	1.0	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—						

機械質量の訂正

改訂

コード		05																		コード		05	
分類コード	規格	諸元	機関力 (kW)	機械質量 (t)	(1) 基礎価格 (千円)	(2) 標準使用 年数 (年)	償却 費率	年間標準			T	t	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転1時間当り 損料額 (円)	(11) 供用1日当り 損料額 (円)	参考		摘要				
								(3) 運転 時間 (時間)	(4) 運転 日数 (日)	(5) 供用 日数 (日)	運転日 当り 標準運 転時間 (時間)	供用日 当り 標準運 転時間 (時間)					(13) 運転1時間当り 換算値 損料額 (円)	(15) 供用1日当り 換算値 損料額 (円)					
0512 クローラ式アースオーガ																							
111 【単軸式・直結三点支持式】																							
045-001	オーガ出力 掘削径 リーダ長 45kW φ 350～800mm 18～21m	117	59.6	81,400	11.5	0.9	630	110	160	5.7	3.9	30	10.0	8,470	81,400	29,300	115,000	ベースマシンは全装備質量66t。					
055-001	55 450～1,000 18～21	117	60.4	84,800	11.5	0.9	630	110	160	5.7	3.9	30	10.0	8,820	84,900	30,600	119,000	ベースマシンは全装備質量66t。					
075-001	75 450～1,000 21～27	114	81.6	106,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,000	106,000	38,200	149,000	ベースマシンは全装備質量95t。					
090-001	90 450～1,200 21～27	114	84.1	109,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,300	109,000	39,200	153,000	ベースマシンは全装備質量95t。					
110-001	55×2 450～1,200 21～33	114	90.2	132,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	13,700	132,000	47,500	186,000	ベースマシンは全装備質量105t。					
150-001	75×2 600～1,200 21～33	136	103	141,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,700	141,000	50,900	198,000	ベースマシンは全装備質量120t。					
180-001	90×2 600～1,800 21～33	136	106	159,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	16,500	159,000	57,300	224,000	ベースマシンは全装備質量120t。					
115 【単軸（油圧）式・直結三点支持式】																							
035-001	掘削トルク 掘削径 リーダ長 29～35kN・m φ 260～600mm 18～21m	117	55.2	78,600	11.5	0.9	630	110	160	5.7	3.9	30	10.0	8,170	78,700	28,300	111,000	ベースマシンは全装備質量66t。					
121 【二軸同軸式・直結三点支持式】																							
055-001	オーガ出力 掘削径 リーダ長 55kW φ 320～600m 21～27mm	114	81.5	107,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,100	107,000	38,500	151,000	ベースマシンは全装備質量95t。					
090-001	90 400～800 21～33	114	89.2	132,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	13,700	132,000	47,500	186,000	ベースマシンは全装備質量105t。					
110-001	55×2 800～1,200 21～33	136	106	150,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,600	151,000	54,300	211,000	ベースマシンは全装備質量120t。					
150-001	75×2 800～1,200 21～36	147	118	167,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	17,400	167,000	60,200	235,000	ベースマシンは全装備質量135t。					
180-001	90×2 800～1,500 21～36	147	118	169,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	17,600	169,000	60,900	238,000	ベースマシンは全装備質量135t。					
199 【0512-111～121付属機器】																							
023-002	【オーガスクリュ】 (各種)	—	—	—	1.7	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—						
024-002	【オーガヘッド】 (各種)	—	—	—	1.0	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—						

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

頁番号	現 行																				摘 要	
建設機械等 損料算定表 P105	- 105 -	コード	05		規格										参 考					コード	05	
		分 類 コ ー ド			規 格	(1)	(2)	償 却	年 間 標 準			T	t	(6)	(7)	(9)	(11)	(13)	(15)	摘 要		
			諸 元	機 関 力	機 械 量	基礎価格	標準使用年数	費 率	(3)	(4)	(5)	運 転 日 当 り	供 用 日 当 り	維持修理費率	年間管理費率	運 転 1 時 間 当 り	供 用 1 日 当 り	運 転 1 時 間 当 り	供 用 1 日 当 り	摘 要		
				出 力	量	(千円)	(年)	(%)	運 転 時間	運 転 日 数	供 用 日 数	標準運転時間	標準運転時間	(%)	(%)	損 料 額	損 料 額	換 算 値	換 算 値			
				(kW)	(t)				(時間)	(日)	(日)	(時間)	(時間)			(円)	(円)	(円)	(円)			
		025-002	〔拡大ヘット〕	(各種)	—	—	—	1.7	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—	[310]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、攪拌ロッド、攪拌スクリュ及び攪拌ヘッドは含まない。	
		026-002	〔ケーシング〕	(各種)	—	—	—	1.7	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—		
		027-002	〔ケーシングヘット〕	(各種)	—	—	—	1.0	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—		
		310 〔三軸式・直結三点支持式〕																				
		090-001	オーガ出力 掘削径 吊能力 リーク長 45×2kW φ500～600mm 50～55t 21～33m	114	59.1	138,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,400	138,000	49,800	194,000	ベースマシンは全装備質量105t。		
		110-001	55×2 500～600 60～65 21～33	136	73.0	146,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,200	146,000	52,600	206,000	ベースマシンは全装備質量120t。		
		150-001	75×2 650～850 60～65 21～36	147	78.3	168,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	17,500	168,000	60,600	236,000	ベースマシンは全装備質量135t。		
		180-001	90×2 800～900 80 21～36	147	98.0	232,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	24,100	232,000	83,600	327,000	ベースマシンは全装備質量180t。		
		319 〔0512-310付属機器〕																			[319]各々1軸当たりの価格。	
		050-610	掘削径 長さ(m) 〔攪拌ロッド〕 φ550～600mm 1.00m	—	0.30	250	1.7	0.9	580	100	140	5.8	4.1	15	8.0	152	708	325	1,340			
		050-620	〔攪拌ロッド〕 550～600 2.00	—	0.40	295	1.7	0.9	580	100	140	5.8	4.1	15	8.0	180	835	384	1,580			
		050-630	〔攪拌ロッド〕 550～600 3.00	—	0.50	380	1.7	0.9	580	100	140	5.8	4.1	15	8.0	231	1,080	494	2,030			
		050-667	〔攪拌ロッド〕 550～600 6.75	—	1.0	811	1.7	0.9	580	100	140	5.8	4.1	15	8.0	494	2,300	1,050	4,340			
		050-810	〔攪拌ロッド〕 650～850 1.00	—	0.30	370	1.7	0.9	580	100	140	5.8	4.1	15	8.0	225	1,050	481	1,980			
		050-820	〔攪拌ロッド〕 650～850 2.00	—	0.40	410	1.7	0.9	580	100	140	5.8	4.1	15	8.0	250	1,160	533	2,190			
050-830	〔攪拌ロッド〕 650～850 3.00	—	0.50	445	1.7	0.9	580	100	140	5.8	4.1	15	8.0	271	1,270	581	2,380					
050-867	〔攪拌ロッド〕 650～850 6.75	—	1.1	815	1.7	0.9	580	100	140	5.8	4.1	15	8.0	496	2,310	1,060	4,360					
060-567	〔攪拌スクリュ〕 550 6.75	—	1.3	1,490	1.7	0.9	580	100	140	5.8	4.1	15	8.0	907	4,220	1,940	7,980					
060-667	〔攪拌スクリュ〕 600 6.75	—	1.4	1,590	1.7	0.9	580	100	140	5.8	4.1	15	8.0	968	4,500	2,070	8,510					
060-867	〔攪拌スクリュ〕 650～850 6.75	—	1.6	1,640	1.7	0.9	580	100	140	5.8	4.1	15	8.0	999	4,650	2,130	8,780					
070-550	〔攪拌ヘッド〕 550	—	0.20	524	1.0	0.9	580	100	140	5.8	4.1	15	8.0	542	2,280	1,100	4,530					
070-600	〔攪拌ヘッド〕 600	—	0.30	635	1.0	0.9	580	100	140	5.8	4.1	15	8.0	657	2,760	1,330	5,490					
070-850	〔攪拌ヘッド〕 650～850	—	0.40	1,130	1.0	0.9	580	100	140	5.8	4.1	15	8.0	1,170	4,920	2,370	9,760					
改 訂																				摘 要		
建設機械等 損料算定表 P105	- 105 -	コード	05		規格										参 考					コード	05	
		分 類 コ ー ド			規 格	(1)	(2)	償 却	年 間 標 準			T	t	(6)	(7)	(9)	(11)	(13)	(15)	摘 要		
			諸 元	機 関 力	機 械 量	基礎価格	標準使用年数	費 率	(3)	(4)	(5)	運 転 日 当 り	供 用 日 当 り	維持修理費率	年間管理費率	運 転 1 時 間 当 り	供 用 1 日 当 り	運 転 1 時 間 当 り	供 用 1 日 当 り	摘 要		
				出 力	量	(千円)	(年)	(%)	運 転 時間	運 転 日 数	供 用 日 数	標準運転時間	標準運転時間	(%)	(%)	損 料 額	損 料 額	換 算 値	換 算 値			
				(kW)	(t)				(時間)	(日)	(日)	(時間)	(時間)			(円)	(円)	(円)	(円)			
		025-002	〔拡大ヘット〕	(各種)	—	—	—	1.7	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—	[310]制御盤、操作盤、中間振止、下部振止及び二次側キャブタイヤ(50m)を含み、攪拌ロッド、攪拌スクリュ及び攪拌ヘッドは含まない。	
		026-002	〔ケーシング〕	(各種)	—	—	—	1.7	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—		
		027-002	〔ケーシングヘット〕	(各種)	—	—	—	1.0	0.9	560	90	140	6.2	4.0	15	8.0	—	—	—	—		
		310 〔三軸式・直結三点支持式〕																				
		090-001	オーガ出力 掘削径 吊能力 リーク長 45×2kW φ500～600mm 50～55t 21～33m	114	87.0	138,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,400	138,000	49,800	194,000	ベースマシンは全装備質量105t。		
		110-001	55×2 500～600 60～65 21～33	136	104	146,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,200	146,000	52,600	206,000	ベースマシンは全装備質量120t。		
		150-001	75×2 650～850 60～65 21～36	147	117	168,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	17,500	168,000	60,600	236,000	ベースマシンは全装備質量135t。		
		180-001	90×2 800～900 80 21～36	147	145	232,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	24,100	232,000	83,600	327,000	ベースマシンは全装備質量180t。		
		319 〔0512-310付属機器〕																			[319]各々1軸当たりの価格。	
		050-610	掘削径 長さ(m) 〔攪拌ロッド〕 φ550～600mm 1.00m	—	0.30	250	1.7	0.9	580	100	140	5.8	4.1	15	8.0	152	708	325	1,340			
		050-620	〔攪拌ロッド〕 550～600 2.00	—	0.40	295	1.7	0.9	580	100	140	5.8	4.1	15	8.0	180	835	384	1,580			
		050-630	〔攪拌ロッド〕 550～600 3.00	—	0.50	380	1.7	0.9	580	100	140	5.8	4.1	15	8.0	231	1,080	494	2,030			
		050-667	〔攪拌ロッド〕 550～600 6.75	—	1.0	811	1.7	0.9	580	100	140	5.8	4.1	15	8.0	494	2,300	1,050	4,340			
		050-810	〔攪拌ロッド〕 650～850 1.00	—	0.30	370	1.7	0.9	580	100	140	5.8	4.1	15	8.0	225	1,050	481	1,980			
		050-820	〔攪拌ロッド〕 650～850 2.00	—	0.40	410	1.7	0.9	580	100	140	5.8	4.1	15	8.0	250	1,160	533	2,190			
050-830	〔攪拌ロッド〕 650～850 3.00	—	0.50	445	1.7	0.9	580	100	140	5.8	4.1	15	8.0	271	1,270	581	2,380					
050-867	〔攪拌ロッド〕 650～850 6.75	—	1.1	815	1.7	0.9	580	100	140	5.8	4.1	15	8.0	496	2,310	1,060	4,360					
060-567	〔攪拌スクリュ〕 550 6.75	—	1.3	1,490	1.7	0.9	580	100	140	5.8	4.1	15	8.0	907	4,220	1,940	7,980					
060-667	〔攪拌スクリュ〕 600 6.75	—	1.4	1,590	1.7	0.9	580	100	140	5.8	4.1	15	8.0	968	4,500	2,070	8,510					
060-867	〔攪拌スクリュ〕 650～850 6.75	—	1.6	1,640	1.7	0.9	580	100	140	5.8	4.1	15	8.0	999	4,650	2,130	8,780					
070-550	〔攪拌ヘッド〕 550	—	0.20	524	1.0	0.9	580	100	140	5.8	4.1	15	8.0	542	2,280	1,100	4,530					
070-600	〔攪拌ヘッド〕 600	—	0.30	635	1.0	0.9	580	100	140	5.8	4.1	15	8.0	657	2,760	1,330	5,490					
070-850	〔攪拌ヘッド〕 650～850	—	0.40	1,130	1.0	0.9	580	100	140	5.8	4.1	15	8.0	1,170	4,920	2,370	9,760					
機 械 質 量 の 訂 正																				摘 要		

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

建設機械等
損料算定表
P106

- 106 -

頁番号		現 行																				摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
建設機械等 損料算定表 P106	- 106 -	<table><tr><th colspan="2">コード</th><th colspan="19">05</th><th colspan="2">コード</th><th colspan="2">05</th></tr><tr><th rowspan="2">分 類 コ ー ド</th><th colspan="3">規 格</th><th rowspan="2">(1) 基礎価格 (千円)</th><th rowspan="2">(2) 標準 使用 年数 (年)</th><th rowspan="2">償 却 費 率</th><th colspan="3">年 間 標 準</th><th rowspan="2">T 運転日 当り 標準運 転時間 (時間)</th><th rowspan="2">t 供用日 当り 標準運 転時間 (時間)</th><th rowspan="2">(6) 維持 修理 費率 (%)</th><th rowspan="2">(7) 年間 管理 費率 (%)</th><th rowspan="2">(9) 運転 1 時間当り 損 料 額 (円)</th><th rowspan="2">(11) 供用 1 日当り 損 料 額 (円)</th><th colspan="3">参 考</th><th rowspan="2">摘 要</th></tr><tr><th>諸 元</th><th>機 関 出 力 (kW)</th><th>機 械 質 量 (t)</th><th>(3) 運 転 時間 (時間)</th><th>(4) 運 転 日 数 (日)</th><th>(5) 供 用 日 数 (日)</th><th>(13) 運 転 1 時間当り 換 算 値 損 料 額 (円)</th><th>(15) 供用 1 日当り 換 算 値 損 料 額 (円)</th></tr><tr><td colspan="2">410 【アースオーガ中掘機・直結三点支持式】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>045-001</td><td>オーガ出力 公称杭径 リーダ長 45kW φ400～1,000mm 21～24m</td><td>92</td><td>57.4</td><td>106,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>11,000</td><td>106,000</td><td>38,200</td><td>149,000</td><td>ベースマシンは全装備質量88t。</td></tr><tr><td>055-001</td><td>55 400～1,200 21～33</td><td>114</td><td>71.0</td><td>150,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>15,600</td><td>151,000</td><td>54,300</td><td>211,000</td><td>ベースマシンは全装備質量105t。</td></tr><tr><td>090-001</td><td>90 400～1,200 21～33</td><td>136</td><td>82.8</td><td>162,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>16,800</td><td>162,000</td><td>58,300</td><td>228,000</td><td>ベースマシンは全装備質量120t。</td></tr><tr><td>110-001</td><td>55×2 600～1,200 21～36</td><td>147</td><td>92.8</td><td>176,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>18,300</td><td>176,000</td><td>63,400</td><td>248,000</td><td>ベースマシンは全装備質量135t。</td></tr><tr><td colspan="2">419 【0512-410付属機器】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>201-002</td><td>〔中掘先端根固め管理装置〕</td><td>—</td><td>—</td><td>4,200</td><td>11.5</td><td>0.9</td><td>590</td><td>100</td><td>150</td><td>5.9</td><td>3.9</td><td>30</td><td>10.0</td><td>466</td><td>4,490</td><td>1,620</td><td>6,310</td><td></td></tr><tr><td colspan="2">510 【アースオーガ併用圧入杭打機】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>045-001</td><td>オーガ出力 適応鋼矢板 リーダ長 45kW II～V型 21～24m</td><td>92</td><td>50.6</td><td>100,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>10,400</td><td>100,000</td><td>36,000</td><td>141,000</td><td>ベースマシンは全装備質量88t。</td></tr><tr><td>046-001</td><td>45 II～V 21～27</td><td>114</td><td>55.2</td><td>116,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>12,100</td><td>116,000</td><td>41,800</td><td>163,000</td><td>ベースマシンは全装備質量95t。</td></tr><tr><td>055-001</td><td>55 II～V 21～33</td><td>114</td><td>60.4</td><td>140,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>14,600</td><td>140,000</td><td>50,500</td><td>197,000</td><td>ベースマシンは全装備質量105t。</td></tr><tr><td>090-001</td><td>90 II～V 21～33</td><td>114</td><td>61.4</td><td>142,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>14,800</td><td>143,000</td><td>51,500</td><td>200,000</td><td>ベースマシンは全装備質量105t。</td></tr><tr><td colspan="2">540 【アースオーガ（油圧式）併用圧入杭打機】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>021-001</td><td>掘削トナリ リーダ長 21kN・m 14.5～15.5m</td><td>86</td><td>41.5</td><td>68,300</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>7,100</td><td>68,300</td><td>24,600</td><td>96,100</td><td>ベースマシンは全装備質量43t。</td></tr><tr><td>034-001</td><td>34 18～21</td><td>117</td><td>45.0</td><td>88,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>9,150</td><td>88,100</td><td>31,700</td><td>124,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="2">0513 アースドリル</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td colspan="2">100 【クローラ型】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>150-043</td><td>最大掘削径 最大掘削長 φ1,500mm 35～43m</td><td>83</td><td>20.0</td><td>44,000</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>4,400</td><td>50,300</td><td>15,300</td><td>70,800</td><td></td></tr><tr><td>170-065</td><td>1,700 43～65</td><td>111</td><td>39.0</td><td>66,300</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>6,630</td><td>75,800</td><td>23,100</td><td>107,000</td><td></td></tr><tr><td>200-058</td><td>2,000 41～58</td><td>124</td><td>50.0</td><td>77,600</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>7,760</td><td>88,700</td><td>27,000</td><td>125,000</td><td></td></tr><tr><td>220-063</td><td>2,200 54～63</td><td>122</td><td>58.0</td><td>80,300</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>8,030</td><td>91,800</td><td>28,000</td><td>129,000</td><td></td></tr></table>																				コード		05																			コード		05		分 類 コ ー ド	規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運転日 当り 標準運 転時間 (時間)	t 供用日 当り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転 1 時間当り 損 料 額 (円)	(11) 供用 1 日当り 損 料 額 (円)	参 考			摘 要	諸 元	機 関 出 力 (kW)	機 械 質 量 (t)	(3) 運 転 時間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)	(13) 運 転 1 時間当り 換 算 値 損 料 額 (円)	(15) 供用 1 日当り 換 算 値 損 料 額 (円)	410 【アースオーガ中掘機・直結三点支持式】																					045-001	オーガ出力 公称杭径 リーダ長 45kW φ400～1,000mm 21～24m	92	57.4	106,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,000	106,000	38,200	149,000	ベースマシンは全装備質量88t。	055-001	55 400～1,200 21～33	114	71.0	150,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,600	151,000	54,300	211,000	ベースマシンは全装備質量105t。	090-001	90 400～1,200 21～33	136	82.8	162,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	16,800	162,000	58,300	228,000	ベースマシンは全装備質量120t。	110-001	55×2 600～1,200 21～36	147	92.8	176,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	18,300	176,000	63,400	248,000	ベースマシンは全装備質量135t。	419 【0512-410付属機器】																				201-002	〔中掘先端根固め管理装置〕	—	—	4,200	11.5	0.9	590	100	150	5.9	3.9	30	10.0	466	4,490	1,620	6,310		510 【アースオーガ併用圧入杭打機】																				045-001	オーガ出力 適応鋼矢板 リーダ長 45kW II～V型 21～24m	92	50.6	100,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	10,400	100,000	36,000	141,000	ベースマシンは全装備質量88t。	046-001	45 II～V 21～27	114	55.2	116,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	12,100	116,000	41,800	163,000	ベースマシンは全装備質量95t。	055-001	55 II～V 21～33	114	60.4	140,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,600	140,000	50,500	197,000	ベースマシンは全装備質量105t。	090-001	90 II～V 21～33	114	61.4	142,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,800	143,000	51,500	200,000	ベースマシンは全装備質量105t。	540 【アースオーガ（油圧式）併用圧入杭打機】																				021-001	掘削トナリ リーダ長 21kN・m 14.5～15.5m	86	41.5	68,300	11.5	0.9	630	110	160	5.7	3.9	30	10.0	7,100	68,300	24,600	96,100	ベースマシンは全装備質量43t。	034-001	34 18～21	117	45.0	88,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	9,150	88,100	31,700	124,000	ベースマシンは全装備質量66t。	0513 アースドリル																				100 【クローラ型】																				150-043	最大掘削径 最大掘削長 φ1,500mm 35～43m	83	20.0	44,000	11.5	0.9	650	110	140	5.9	4.6	30	10.0	4,400	50,300	15,300	70,800		170-065	1,700 43～65	111	39.0	66,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	6,630	75,800	23,100	107,000		200-058	2,000 41～58	124	50.0	77,600	11.5	0.9	650	110	140	5.9	4.6	30	10.0	7,760	88,700	27,000	125,000		220-063	2,200 54～63	122	58.0	80,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	8,030	91,800	28,000	129,000	
		コード		05																			コード		05																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
		分 類 コ ー ド	規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運転日 当り 標準運 転時間 (時間)	t 供用日 当り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転 1 時間当り 損 料 額 (円)	(11) 供用 1 日当り 損 料 額 (円)	参 考			摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
			諸 元	機 関 出 力 (kW)	機 械 質 量 (t)				(3) 運 転 時間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)							(13) 運 転 1 時間当り 換 算 値 損 料 額 (円)	(15) 供用 1 日当り 換 算 値 損 料 額 (円)																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
		410 【アースオーガ中掘機・直結三点支持式】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
		045-001	オーガ出力 公称杭径 リーダ長 45kW φ400～1,000mm 21～24m	92	57.4	106,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,000	106,000	38,200	149,000	ベースマシンは全装備質量88t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		055-001	55 400～1,200 21～33	114	71.0	150,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,600	151,000	54,300	211,000	ベースマシンは全装備質量105t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		090-001	90 400～1,200 21～33	136	82.8	162,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	16,800	162,000	58,300	228,000	ベースマシンは全装備質量120t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		110-001	55×2 600～1,200 21～36	147	92.8	176,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	18,300	176,000	63,400	248,000	ベースマシンは全装備質量135t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		419 【0512-410付属機器】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
201-002	〔中掘先端根固め管理装置〕	—	—	4,200	11.5	0.9	590	100	150	5.9	3.9	30	10.0	466	4,490	1,620	6,310																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
510 【アースオーガ併用圧入杭打機】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
045-001	オーガ出力 適応鋼矢板 リーダ長 45kW II～V型 21～24m	92	50.6	100,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	10,400	100,000	36,000	141,000	ベースマシンは全装備質量88t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
046-001	45 II～V 21～27	114	55.2	116,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	12,100	116,000	41,800	163,000	ベースマシンは全装備質量95t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
055-001	55 II～V 21～33	114	60.4	140,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,600	140,000	50,500	197,000	ベースマシンは全装備質量105t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
090-001	90 II～V 21～33	114	61.4	142,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,800	143,000	51,500	200,000	ベースマシンは全装備質量105t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
540 【アースオーガ（油圧式）併用圧入杭打機】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
021-001	掘削トナリ リーダ長 21kN・m 14.5～15.5m	86	41.5	68,300	11.5	0.9	630	110	160	5.7	3.9	30	10.0	7,100	68,300	24,600	96,100	ベースマシンは全装備質量43t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
034-001	34 18～21	117	45.0	88,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	9,150	88,100	31,700	124,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
0513 アースドリル																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
100 【クローラ型】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
150-043	最大掘削径 最大掘削長 φ1,500mm 35～43m	83	20.0	44,000	11.5	0.9	650	110	140	5.9	4.6	30	10.0	4,400	50,300	15,300	70,800																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
170-065	1,700 43～65	111	39.0	66,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	6,630	75,800	23,100	107,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
200-058	2,000 41～58	124	50.0	77,600	11.5	0.9	650	110	140	5.9	4.6	30	10.0	7,760	88,700	27,000	125,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
220-063	2,200 54～63	122	58.0	80,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	8,030	91,800	28,000	129,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
改 訂																						摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
建設機械等 損料算定表 P106	- 106 -	<table><tr><th colspan="2">コード</th><th colspan="19">05</th><th colspan="2">コード</th><th colspan="2">05</th></tr><tr><th rowspan="2">分 類 コ ー ド</th><th colspan="3">規 格</th><th rowspan="2">(1) 基礎価格 (千円)</th><th rowspan="2">(2) 標準 使用 年数 (年)</th><th rowspan="2">償 却 費 率</th><th colspan="3">年 間 標 準</th><th rowspan="2">T 運転日 当り 標準運 転時間 (時間)</th><th rowspan="2">t 供用日 当り 標準運 転時間 (時間)</th><th rowspan="2">(6) 維持 修理 費率 (%)</th><th rowspan="2">(7) 年間 管理 費率 (%)</th><th rowspan="2">(9) 運転 1 時間当り 損 料 額 (円)</th><th rowspan="2">(11) 供用 1 日当り 損 料 額 (円)</th><th colspan="3">参 考</th><th rowspan="2">摘 要</th></tr><tr><th>諸 元</th><th>機 関 出 力 (kW)</th><th>機 械 質 量 (t)</th><th>(3) 運 転 時間 (時間)</th><th>(4) 運 転 日 数 (日)</th><th>(5) 供 用 日 数 (日)</th><th>(13) 運 転 1 時間当り 換 算 値 損 料 額 (円)</th><th>(15) 供用 1 日当り 換 算 値 損 料 額 (円)</th></tr><tr><td colspan="2">410 【アースオーガ中掘機・直結三点支持式】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>045-001</td><td>オーガ出力 公称杭径 リーダ長 45kW φ400～1,000mm 21～24m</td><td>92</td><td>76.3</td><td>106,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>11,000</td><td>106,000</td><td>38,200</td><td>149,000</td><td>ベースマシンは全装備質量88t。</td></tr><tr><td>055-001</td><td>55 400～1,200 21～33</td><td>114</td><td>98.9</td><td>150,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>15,600</td><td>151,000</td><td>54,300</td><td>211,000</td><td>ベースマシンは全装備質量105t。</td></tr><tr><td>090-001</td><td>90 400～1,200 21～33</td><td>136</td><td>115</td><td>162,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>16,800</td><td>162,000</td><td>58,300</td><td>228,000</td><td>ベースマシンは全装備質量120t。</td></tr><tr><td>110-001</td><td>55×2 600～1,200 21～36</td><td>147</td><td>131</td><td>176,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>18,300</td><td>176,000</td><td>63,400</td><td>248,000</td><td>ベースマシンは全装備質量135t。</td></tr><tr><td colspan="2">419 【0512-410付属機器】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>201-002</td><td>〔中掘先端根固め管理装置〕</td><td>—</td><td>—</td><td>4,200</td><td>11.5</td><td>0.9</td><td>590</td><td>100</td><td>150</td><td>5.9</td><td>3.9</td><td>30</td><td>10.0</td><td>466</td><td>4,490</td><td>1,620</td><td>6,310</td><td></td></tr><tr><td colspan="2">510 【アースオーガ併用圧入杭打機】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>045-001</td><td>オーガ出力 適応鋼矢板 リーダ長 45kW II～V型 21～24m</td><td>92</td><td>67.9</td><td>100,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>10,400</td><td>100,000</td><td>36,000</td><td>141,000</td><td>ベースマシンは全装備質量88t。</td></tr><tr><td>046-001</td><td>45 II～V 21～27</td><td>114</td><td>83.2</td><td>116,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>12,100</td><td>116,000</td><td>41,800</td><td>163,000</td><td>ベースマシンは全装備質量95t。</td></tr><tr><td>055-001</td><td>55 II～V 21～33</td><td>114</td><td>88.3</td><td>140,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>14,600</td><td>140,000</td><td>50,500</td><td>197,000</td><td>ベースマシンは全装備質量105t。</td></tr><tr><td>090-001</td><td>90 II～V 21～33</td><td>114</td><td>89.3</td><td>142,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>14,800</td><td>143,000</td><td>51,500</td><td>200,000</td><td>ベースマシンは全装備質量105t。</td></tr><tr><td colspan="2">540 【アースオーガ（油圧式）併用圧入杭打機】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>021-001</td><td>掘削トナリ リーダ長 21kN・m 14.5～15.5m</td><td>86</td><td>40.9</td><td>68,300</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>7,100</td><td>68,300</td><td>24,600</td><td>96,100</td><td>ベースマシンは全装備質量43t。</td></tr><tr><td>034-001</td><td>34 18～21</td><td>117</td><td>59.8</td><td>88,000</td><td>11.5</td><td>0.9</td><td>630</td><td>110</td><td>160</td><td>5.7</td><td>3.9</td><td>30</td><td>10.0</td><td>9,150</td><td>88,100</td><td>31,700</td><td>124,000</td><td>ベースマシンは全装備質量66t。</td></tr><tr><td colspan="2">0513 アースドリル</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td colspan="2">100 【クローラ型】</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>150-043</td><td>最大掘削径 最大掘削長 φ1,500mm 35～43m</td><td>83</td><td>20.0</td><td>44,000</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>4,400</td><td>50,300</td><td>15,300</td><td>70,800</td><td></td></tr><tr><td>170-065</td><td>1,700 43～65</td><td>111</td><td>39.0</td><td>66,300</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>6,630</td><td>75,800</td><td>23,100</td><td>107,000</td><td></td></tr><tr><td>200-058</td><td>2,000 41～58</td><td>124</td><td>50.0</td><td>77,600</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>7,760</td><td>88,700</td><td>27,000</td><td>125,000</td><td></td></tr><tr><td>220-063</td><td>2,200 54～63</td><td>122</td><td>58.0</td><td>80,300</td><td>11.5</td><td>0.9</td><td>650</td><td>110</td><td>140</td><td>5.9</td><td>4.6</td><td>30</td><td>10.0</td><td>8,030</td><td>91,800</td><td>28,000</td><td>129,000</td><td></td></tr></table>																				コード		05																			コード		05		分 類 コ ー ド	規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運転日 当り 標準運 転時間 (時間)	t 供用日 当り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転 1 時間当り 損 料 額 (円)	(11) 供用 1 日当り 損 料 額 (円)	参 考			摘 要	諸 元	機 関 出 力 (kW)	機 械 質 量 (t)	(3) 運 転 時間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)	(13) 運 転 1 時間当り 換 算 値 損 料 額 (円)	(15) 供用 1 日当り 換 算 値 損 料 額 (円)	410 【アースオーガ中掘機・直結三点支持式】																					045-001	オーガ出力 公称杭径 リーダ長 45kW φ400～1,000mm 21～24m	92	76.3	106,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,000	106,000	38,200	149,000	ベースマシンは全装備質量88t。	055-001	55 400～1,200 21～33	114	98.9	150,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,600	151,000	54,300	211,000	ベースマシンは全装備質量105t。	090-001	90 400～1,200 21～33	136	115	162,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	16,800	162,000	58,300	228,000	ベースマシンは全装備質量120t。	110-001	55×2 600～1,200 21～36	147	131	176,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	18,300	176,000	63,400	248,000	ベースマシンは全装備質量135t。	419 【0512-410付属機器】																				201-002	〔中掘先端根固め管理装置〕	—	—	4,200	11.5	0.9	590	100	150	5.9	3.9	30	10.0	466	4,490	1,620	6,310		510 【アースオーガ併用圧入杭打機】																				045-001	オーガ出力 適応鋼矢板 リーダ長 45kW II～V型 21～24m	92	67.9	100,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	10,400	100,000	36,000	141,000	ベースマシンは全装備質量88t。	046-001	45 II～V 21～27	114	83.2	116,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	12,100	116,000	41,800	163,000	ベースマシンは全装備質量95t。	055-001	55 II～V 21～33	114	88.3	140,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,600	140,000	50,500	197,000	ベースマシンは全装備質量105t。	090-001	90 II～V 21～33	114	89.3	142,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,800	143,000	51,500	200,000	ベースマシンは全装備質量105t。	540 【アースオーガ（油圧式）併用圧入杭打機】																				021-001	掘削トナリ リーダ長 21kN・m 14.5～15.5m	86	40.9	68,300	11.5	0.9	630	110	160	5.7	3.9	30	10.0	7,100	68,300	24,600	96,100	ベースマシンは全装備質量43t。	034-001	34 18～21	117	59.8	88,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	9,150	88,100	31,700	124,000	ベースマシンは全装備質量66t。	0513 アースドリル																				100 【クローラ型】																				150-043	最大掘削径 最大掘削長 φ1,500mm 35～43m	83	20.0	44,000	11.5	0.9	650	110	140	5.9	4.6	30	10.0	4,400	50,300	15,300	70,800		170-065	1,700 43～65	111	39.0	66,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	6,630	75,800	23,100	107,000		200-058	2,000 41～58	124	50.0	77,600	11.5	0.9	650	110	140	5.9	4.6	30	10.0	7,760	88,700	27,000	125,000		220-063	2,200 54～63	122	58.0	80,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	8,030	91,800	28,000	129,000	
		コード		05																			コード		05																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
		分 類 コ ー ド	規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運転日 当り 標準運 転時間 (時間)	t 供用日 当り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転 1 時間当り 損 料 額 (円)	(11) 供用 1 日当り 損 料 額 (円)	参 考			摘 要																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
			諸 元	機 関 出 力 (kW)	機 械 質 量 (t)				(3) 運 転 時間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)							(13) 運 転 1 時間当り 換 算 値 損 料 額 (円)	(15) 供用 1 日当り 換 算 値 損 料 額 (円)																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
		410 【アースオーガ中掘機・直結三点支持式】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
		045-001	オーガ出力 公称杭径 リーダ長 45kW φ400～1,000mm 21～24m	92	76.3	106,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	11,000	106,000	38,200	149,000	ベースマシンは全装備質量88t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		055-001	55 400～1,200 21～33	114	98.9	150,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	15,600	151,000	54,300	211,000	ベースマシンは全装備質量105t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		090-001	90 400～1,200 21～33	136	115	162,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	16,800	162,000	58,300	228,000	ベースマシンは全装備質量120t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		110-001	55×2 600～1,200 21～36	147	131	176,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	18,300	176,000	63,400	248,000	ベースマシンは全装備質量135t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
		419 【0512-410付属機器】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
201-002	〔中掘先端根固め管理装置〕	—	—	4,200	11.5	0.9	590	100	150	5.9	3.9	30	10.0	466	4,490	1,620	6,310																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
510 【アースオーガ併用圧入杭打機】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
045-001	オーガ出力 適応鋼矢板 リーダ長 45kW II～V型 21～24m	92	67.9	100,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	10,400	100,000	36,000	141,000	ベースマシンは全装備質量88t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
046-001	45 II～V 21～27	114	83.2	116,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	12,100	116,000	41,800	163,000	ベースマシンは全装備質量95t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
055-001	55 II～V 21～33	114	88.3	140,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,600	140,000	50,500	197,000	ベースマシンは全装備質量105t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
090-001	90 II～V 21～33	114	89.3	142,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	14,800	143,000	51,500	200,000	ベースマシンは全装備質量105t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
540 【アースオーガ（油圧式）併用圧入杭打機】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
021-001	掘削トナリ リーダ長 21kN・m 14.5～15.5m	86	40.9	68,300	11.5	0.9	630	110	160	5.7	3.9	30	10.0	7,100	68,300	24,600	96,100	ベースマシンは全装備質量43t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
034-001	34 18～21	117	59.8	88,000	11.5	0.9	630	110	160	5.7	3.9	30	10.0	9,150	88,100	31,700	124,000	ベースマシンは全装備質量66t。																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
0513 アースドリル																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
100 【クローラ型】																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
150-043	最大掘削径 最大掘削長 φ1,500mm 35～43m	83	20.0	44,000	11.5	0.9	650	110	140	5.9	4.6	30	10.0	4,400	50,300	15,300	70,800																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
170-065	1,700 43～65	111	39.0	66,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	6,630	75,800	23,100	107,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
200-058	2,000 41～58	124	50.0	77,600	11.5	0.9	650	110	140	5.9	4.6	30	10.0	7,760	88,700	27,000	125,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
220-063	2,200 54～63	122	58.0	80,300	11.5	0.9	650	110	140	5.9	4.6	30	10.0	8,030	91,800	28,000	129,000																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
機 械 質 量 の 訂 正																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

頁番号	現 行																			摘 要	
建設機械等 損料算定表 P121	- 121 -	コード	05																コード	05	
		分類コード		規 格	(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転時間 (時間)	t 供 用 日 当 り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転1時間当り 損 料 額 (円)	(11) 供用1日当り 損 料 額 (円)	(13) 運転1時間当り 換 算 値 損 料 額 (円)	(15) 供用1日当り 換 算 値 損 料 額 (円)	摘 要		
		0553 側壁測定装置																			
		017 〔2方向切換測定式〕																			
		110-001	測定深度 108m	測定幅 300～4,000mm	—	0.10		—	90	130	—	(B) 0.69	40	8.0	(B) 4,380	4,970	(B) 11,600	8,000			
		027 〔4方向同時測定式〕																			
		100-001	測定深度 100m		—	0.20		—	90	130	—	(B) 0.69	40	8.0	(B) 5,840	6,620	(B) 15,400	10,700			
		150-001	150		—	0.60		—	90	130	—	(B) 0.69	40	8.0	(B) 14,200	16,100	(B) 37,500	26,000			
		(地盤改良機器)																			
		0561 深層混合処理機 (スラリー式)																		[0561]施工管理計、システム管理計を含む。	
		100 〔単軸式〕																		[100]管理装置、制御盤、操作盤、中間振止、下部振止、二次側キャブタイヤ(50m)、攪拌軸及び攪拌翼を含み、オーガスクリュ、オーガヘッドは含まない。	
		045-161	モータ出力 45kW×1	杭径 φ1,000～1,600mm	最大施工深度 10m	117	42.7	680	120	180	5.7	3.8	35	10.0	10,300	89,800	33,900	129,000		ベースマシンは全装備質量66t。	
		110-162	90×1	1,000～1,600	20	92	54.4	680	120	180	5.7	3.8	35	10.0	15,000	131,000	49,500	187,000		ベースマシンは全装備質量88t。	
		110-163	90×1	1,000～1,600	30	92	55.4	680	120	180	5.7	3.8	35	10.0	16,700	146,000	55,100	209,000		ベースマシンは全装備質量88t。	
		180-203	90×2	1,800～2,000	27	147	84.1	680	120	180	5.7	3.8	35	10.0	19,900	174,000	65,700	249,000		ベースマシンは全装備質量135t。	
		200 〔二軸式〕																		[200]変位低減型を使用する場合は、基礎価格を5%増とする。分離型は除く。管理装置、制御盤、操作盤、中間振止、下部振止、二次側キャブタイヤ(50m)、攪拌軸及び攪拌翼を含み、オーガスクリュ、オーガヘッド、ケーシング及びケーシングヘッドは含まない。	
		090-101	モータ出力 45kW×2	杭径 φ1,000mm	最大施工深度 10m	117	48.3	680	120	180	5.7	3.8	35	10.0	11,700	102,000	38,500	147,000		ベースマシンは全装備質量66t。	
		120-102	55～60×2	1,000	20	92	61.2	680	120	180	5.7	3.8	35	10.0	13,900	121,000	45,700	173,000		ベースマシンは全装備質量88t。	
		180-103	75～90×2	1,000	30	114	73.0	680	120	180	5.7	3.8	35	10.0	18,500	161,000	60,900	231,000		ベースマシンは全装備質量105t。	
		180-104	90×2	1,000	40	147	109	680	120	180	5.7	3.8	35	10.0	26,700	233,000	88,000	334,000		ベースマシンは全装備質量180t。	
		180-121	75～90×2	1,200	10	114	64.3	680	120	180	5.7	3.8	35	10.0	15,800	138,000	52,100	198,000		ベースマシンは全装備質量95t。	
		180-122	90×2	1,200	20	136	81.1	680	120	180	5.7	3.8	35	10.0	19,100	167,000	63,000	238,000		ベースマシンは全装備質量120t。	
		180-131	90×2	1,300	10	114	69.4	680	120	180	5.7	3.8	35	10.0	18,300	159,000	60,100	228,000		ベースマシンは全装備質量105t。	
		220-123	90×2	1,200	30	147	90.2	680	120	180	5.7	3.8	35	10.0	20,500	178,000	67,300	256,000		ベースマシンは全装備質量135t。	
改 訂																			摘 要		
	- 121 -	コード	05																コード	05	
		分類コード		規 格	(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転時間 (時間)	t 供 用 日 当 り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運転1時間当り 損 料 額 (円)	(11) 供用1日当り 損 料 額 (円)	(13) 運転1時間当り 換 算 値 損 料 額 (円)	(15) 供用1日当り 換 算 値 損 料 額 (円)	摘 要		
		0553 側壁測定装置																			
		017 〔2方向切換測定式〕																			
		110-001	測定深度 108m	測定幅 300～4,000mm	—	0.10		—	90	130	—	(B) 0.69	40	8.0	(B) 4,380	4,970	(B) 11,600	8,000			
		027 〔4方向同時測定式〕																			
		100-001	測定深度 100m		—	0.20		—	90	130	—	(B) 0.69	40	8.0	(B) 5,840	6,620	(B) 15,400	10,700			
		150-001	150		—	0.60		—	90	130	—	(B) 0.69	40	8.0	(B) 14,200	16,100	(B) 37,500	26,000			
		(地盤改良機器)																			
		0561 深層混合処理機 (スラリー式)																		[0561]施工管理計、システム管理計を含む。	
		100 〔単軸式〕																		[100]管理装置、制御盤、操作盤、中間振止、下部振止、二次側キャブタイヤ(50m)、攪拌軸及び攪拌翼を含み、オーガスクリュ、オーガヘッドは含まない。	
		045-161	モータ出力 45kW×1	杭径 φ1,000～1,600mm	最大施工深度 10m	117	63.6	680	120	180	5.7	3.8	35	10.0	10,300	89,800	33,900	129,000		ベースマシンは全装備質量66t。	
		110-162	90×1	1,000～1,600	20	92	76.8	680	120	180	5.7	3.8	35	10.0	15,000	131,000	49,500	187,000		ベースマシンは全装備質量88t。	
		110-163	90×1	1,000～1,600	30	92	80.8	680	120	180	5.7	3.8	35	10.0	16,700	146,000	55,100	209,000		ベースマシンは全装備質量88t。	
		180-203	90×2	1,800～2,000	27	147	129	680	120	180	5.7	3.8	35	10.0	19,900	174,000	65,700	249,000		ベースマシンは全装備質量135t。	
		200 〔二軸式〕																		[200]変位低減型を使用する場合は、基礎価格を5%増とする。分離型は除く。管理装置、制御盤、操作盤、中間振止、下部振止、二次側キャブタイヤ(50m)、攪拌軸及び攪拌翼を含み、オーガスクリュ、オーガヘッド、ケーシング及びケーシングヘッドは含まない。	
		090-101	モータ出力 45kW×2	杭径 φ1,000mm	最大施工深度 10m	117	64.9	680	120	180	5.7	3.8	35	10.0	11,700	102,000	38,500	147,000		ベースマシンは全装備質量66t。	
		120-102	55～60×2	1,000	20	92	81.8	680	120	180	5.7	3.8	35	10.0	13,900	121,000	45,700	173,000		ベースマシンは全装備質量88t。	
		180-103	75～90×2	1,000	30	114	104	680	120	180	5.7	3.8	35	10.0	18,500	161,000	60,900	231,000		ベースマシンは全装備質量105t。	
		180-104	90×2	1,000	40	147	160	680	120	180	5.7	3.8	35	10.0	26,700	233,000	88,000	334,000		ベースマシンは全装備質量180t。	
		180-121	75～90×2	1,200	10	114	92.9	680	120	180	5.7	3.8	35	10.0	15,800	138,000	52,100	198,000		ベースマシンは全装備質量95t。	
		180-122	90×2	1,200	20	136	116	680	120	180	5.7	3.8	35	10.0	19,100	167,000	63,000	238,000		ベースマシンは全装備質量120t。	
		180-131	90×2	1,300	10	114	98.4	680	120	180	5.7	3.8	35	10.0	18,300	159,000	60,100	228,000		ベースマシンは全装備質量105t。	
		220-123	90×2	1,200	30	147	134	680	120	180	5.7	3.8	35	10.0	20,500	178,000	67,300	256,000		ベースマシンは全装備質量135t。	
																			摘 要		
																			機械質量の訂正		

令和7年度版建設機械等損料算定表 新旧表(令和7年10月14日 改訂)

頁番号	現 行																				摘 要					
建設機械等 損料算定表 P122	- 122 -	コード	05																コード	05						
		分 類 コ ー ド	規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転時間 (時間)	t 供 用 日 当 り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運 転 1 時間 当 り 損 料 額 (円)	(11) 供 用 1 日 当 り 損 料 額 (円)	(13)	(15)	摘 要						
			諸 元	機 関 力 (kW)	機 械 質 量 (t)				(3) 運 転 時間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)							運 転 1 時間 当 り 換 算 値 損 料 額 (円)	供 用 1 日 当 り 換 算 値 損 料 額 (円)							
		220-124	90×2	1,200	40	147	93.0	232,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	23,700	206,000	77,900	296,000		ベースマシンは全装備質量135t。			
		220-132	90×2	1,300	20	147	87.5	199,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	20,300	177,000	66,900	254,000		ベースマシンは全装備質量135t。			
		220-133	90×2	1,300	30	147	90.3	208,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	21,200	185,000	69,900	265,000		ベースマシンは全装備質量135t。			
		300	〔二軸式・変位低減型〕																				[300]分離型は除く。管理装置、制御盤、操作盤、中間振止、下部振止、二次側キャブタイヤ(50m)、攪拌軸及び攪拌翼を含み、オーガスクリュー、オーガヘッド、ケーシング及びケーシングヘッドは含まない。			
		180-161	モータ出力 90kW×2	杭径 φ1,600mm	最大施工深度 10m	114	64.5	170,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	17,300	151,000	57,000	217,000		ベースマシンは全装備質量95t。			
		180-162	90×2	1,600	20	114	73.2	207,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	21,100	184,000	69,500	264,000		ベースマシンは全装備質量105t。			
		180-163	90×2	1,600	26	147	90.3	248,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	25,300	221,000	83,500	316,000		ベースマシンは全装備質量135t。			
		180-164	90×2	1,600	36	147	93.1	254,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	25,900	225,000	85,100	324,000		ベースマシンは全装備質量135t。			
		500	〔単軸式・小型地盤改良機〕																				[500]1kN・m÷0.102t・m			
		009-001	全装備質量 6～9t	掘削トルク 11.2kN・m	改良径 φ600～800mm	33	7.6	41,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	4,510	35,400	12,700	54,700					
		011-001	11	22.2	800～1,000	56	11.5	48,200	9.0	0.9	860	160	200	5.4	4.3	40	10.0	5,300	41,600	15,000	64,300					
		013-001	13	27.4	800～1,300	71	13.1	49,400	9.0	0.9	860	160	200	5.4	4.3	40	10.0	5,430	42,700	15,400	65,900					
		015-001	17.6	39.0	1,000～1,300	92	17.6	62,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	6,820	53,500	19,300	82,800					
		030-001	25～30	71.1	1,200～1,400	92	25.5	74,200	9.0	0.9	860	160	200	5.4	4.3	40	10.0	8,160	64,100	23,100	99,000					
		037-001	37	100	～1,500	160	37.3	101,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	11,100	87,200	31,400	135,000					
		047-001	47	131	～1,500	160	46.7	136,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	15,000	117,000	42,200	182,000					
		999	〔0561-100～500付属機器〕																				[999]スクリュコンベア、セメントサイロ、水槽、水中ポンプ、アジテータ、グラウトポンプ及びスラリープラント制御盤各1基を含む。			
		028-010	〔スリプラント（全自動）〕	能力 10m ³ /h		78	14.0	33,100	12.0	0.9	670	110	170	6.1	3.9	45	10.0	3,710	30,800	11,600	45,400					
		028-020	〔スリプラント（全自動）〕	20		102	17.0	39,200	12.0	0.9	670	110	170	6.1	3.9	45	10.0	4,390	36,500	13,700	53,800					
		028-040	〔スリプラント（全自動）〕	40		173	23.4	48,000	12.0	0.9	670	110	170	6.1	3.9	45	10.0	5,380	44,600	16,800	65,800					
		0562	高圧噴射攪拌式地盤改良機																							
		110	〔掘削専用型（油圧式）〕																							
110-001	スピンドル内径	φ148mm		11	1.5	9,960	12.0	0.9	—	100	130	—	(B)0.77	65	10.0	(B)9,130	12,100	(B)24,800	19,100							
改 訂																										
建設機械等 損料算定表 P122	- 122 -	コード	05																コード	05		機械質量の訂正 摘要欄 全装備質量の訂正				
		分 類 コ ー ド	規 格			(1) 基礎価格 (千円)	(2) 標準 使用 年数 (年)	償 却 費 率	年 間 標 準			T 運 転 日 当 り 標準運 転時間 (時間)	t 供 用 日 当 り 標準運 転時間 (時間)	(6) 維持 修理 費率 (%)	(7) 年間 管理 費率 (%)	(9) 運 転 1 時間 当 り 損 料 額 (円)	(11) 供 用 1 日 当 り 損 料 額 (円)	(13)	(15)	摘 要						
			諸 元	機 関 力 (kW)	機 械 質 量 (t)				(3) 運 転 時間 (時間)	(4) 運 転 日 数 (日)	(5) 供 用 日 数 (日)							運 転 1 時間 当 り 換 算 値 損 料 額 (円)	供 用 1 日 当 り 換 算 値 損 料 額 (円)							
		220-124	90×2	1,200	40	147	164	232,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	23,700	206,000	77,900	296,000		ベースマシンは全装備質量180t。			
		220-132	90×2	1,300	20	147	128	199,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	20,300	177,000	66,900	254,000		ベースマシンは全装備質量135t。			
		220-133	90×2	1,300	30	147	132	208,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	21,200	185,000	69,900	265,000		ベースマシンは全装備質量135t。			
		300	〔二軸式・変位低減型〕																				[300]分離型は除く。管理装置、制御盤、操作盤、中間振止、下部振止、二次側キャブタイヤ(50m)、攪拌軸及び攪拌翼を含み、オーガスクリュー、オーガヘッド、ケーシング及びケーシングヘッドは含まない。			
		180-161	モータ出力 90kW×2	杭径 φ1,600mm	最大施工深度 10m	114	112	170,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	17,300	151,000	57,000	217,000		ベースマシンは全装備質量120t。			
		180-162	90×2	1,600	20	114	126	207,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	21,100	184,000	69,500	264,000		ベースマシンは全装備質量135t。			
		180-163	90×2	1,600	26	147	148	248,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	25,300	221,000	83,500	316,000		ベースマシンは全装備質量160t。			
		180-164	90×2	1,600	36	147	174	254,000	11.5	0.9	680	120	180	5.7	3.8	35	10.0	25,900	225,000	85,100	324,000		ベースマシンは全装備質量180t。			
		500	〔単軸式・小型地盤改良機〕																				[500]1kN・m÷0.102t・m			
		009-001	全装備質量 6～9t	掘削トルク 11.2kN・m	改良径 φ600～800mm	33	7.6	41,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	4,510	35,400	12,700	54,700					
		011-001	11	22.2	800～1,000	56	11.5	48,200	9.0	0.9	860	160	200	5.4	4.3	40	10.0	5,300	41,600	15,000	64,300					
		013-001	13	27.4	800～1,300	71	13.1	49,400	9.0	0.9	860	160	200	5.4	4.3	40	10.0	5,430	42,700	15,400	65,900					
		015-001	17.6	39.0	1,000～1,300	92	17.6	62,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	6,820	53,500	19,300	82,800					
		030-001	25～30	71.1	1,200～1,400	92	25.5	74,200	9.0	0.9	860	160	200	5.4	4.3	40	10.0	8,160	64,100	23,100	99,000					
		037-001	37	100	～1,500	160	37.3	101,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	11,100	87,200	31,400	135,000					
047-001	47	131	～1,500	160	46.7	136,000	9.0	0.9	860	160	200	5.4	4.3	40	10.0	15,000	117,000	42,200	182,000							
999	〔0561-100～500付属機器〕																			[999]スクリュコンベア、セメントサイロ、水槽、水中ポンプ、アジテータ、グラウトポンプ及びスラリープラント制御盤各1基を含む。						
028-010	〔スリプラント（全自動）〕	能力 10m ³ /h		78	14.0	33,100	12.0	0.9	670	110	170	6.1	3.9	45	10.0	3,710	30,800	11,600	45,400							
028-020	〔スリプラント（全自動）〕	20		102	17.0	39,200	12.0	0.9	670	110	170	6.1	3.9	45	10.0	4,390	36,500	13,700	53,800							
028-040	〔スリプラント（全自動）〕	40		173	23.4	48,000	12.0	0.9	670	110	170	6.1	3.9	45	10.0	5,380	44,600	16,800	65,800							
0562	高圧噴射攪拌式地盤改良機																									
110	〔掘削専用型（油圧式）〕																									
110-001	スピンドル内径	φ148mm		11	1.5	9,960	12.0	0.9	—	100	130	—	(B)0.77	65	10.0	(B)9,130	12,100	(B)24,800	19,100							